

帝国cms灵动标签调用归档信息

1、调用所有

```
[e:loop={"select * from {$dbtbpre}ecms_news_doc order by id desc limit 20",0,24,0}]  
<li>  
<?=$bqno?><a href="<?=$bqsr[classurl]?>" title="<?=$bqsr[classname]?>"><?=$bqsr[classname]?></a>  
<a href="<?=$bqsr[titleurl]?>" title="<?=$bqr[title]?>"><?=esub($bqr[title],40)?></a>  
</li>  
[/e:loop]
```

2、当前栏目或指定栏目

```
[e:loop={"select * from {$dbtbpre}ecms_news_doc where classid=$GLOBALS[navclassid] order by id desc limit 20",0,24,0}]  
<li>  
<?=$bqno?><a href="<?=$bqsr[classurl]?>" title="<?=$bqsr[classname]?>"><?=$bqsr[classname]?></a>  
<a href="<?=$bqsr[titleurl]?>" title="<?=$bqr[title]?>"><?=esub($bqr[title],40)?></a>  
</li>  
[/e:loop]
```

注释：指定多个栏目用 classid=\$GLOBALS[navclassid] 替换为 classid id (34,35,36,37))

3、调用指定信息

```
[e:loop={"select * from {$dbtbpre}ecms_news_doc where classid=34 and id=462 order by id desc limit 20",0,24,0}]  
<li>  
<?=$bqno?><a href="<?=$bqsr[classurl]?>" title="<?=$bqsr[classname]?>"><?=$bqsr[classname]?></a>  
<a href="<?=$bqsr[titleurl]?>" title="<?=$bqr[title]?>"><?=esub($bqr[title],40)?></a>  
</li>
```

```
[/e:loop]
```

3、调用指定范围的信息

```
[e:loop={"select * from {$dbtbpre}ecms_news_doc where id<=46  
2 and id>=262 order by id desc limit 20",0,24,0}]  
<li>  
<?=$bqno?><a href="<?=$bqsr[classurl]?>" title="<?=$bqsr[cl  
assname]?>"><?=$bqsr[classname]?></a>  
<a href="<?=$bqsr[titleurl]?>" title="<?=$bqr[title]?>"><?=  
sub($bqr[title],40)?></a>  
</li>  
[/e:loop]
```